


* 0 3 M 0 4 C 1 9 *



INSTRUCTION MANUAL

Model ADO-102

Serial EC 3497-3


 **elin** DIVISION ● CALIFORNIA INSTRUMENTS CORPORATION

3511 MIDWAY DRIVE / SAN DIEGO, CALIFORNIA 92110

MP MASTER



MA28054



INSTRUCTION MANUAL

Model ADD-102

Serial EC 3497-3

ONE YEAR WARRANTY

CALIFORNIA INSTRUMENTS CORPORATION warrants each instrument manufactured by them to be free from defects in material and workmanship for a period of one year from the date of shipment to the original purchaser. Excepted from this warranty are tubes, fuses, and batteries which carry the warranty of their original manufacturer where applicable. CALIFORNIA INSTRUMENTS CORPORATION will service, replace, or adjust any defective part or parts, free of charge, when the instrument is returned to the Company, freight prepaid, and when examination reveals that the fault has not occurred because of misuse or abnormal conditions of operation. Equipment repaired beyond the effective date of warranty or when abnormal usage has occurred will be charged at applicable rates. CALICO will submit an estimate for such charges before commencing repair if so requested.

PROCEDURE FOR SERVICE

If a fault develops, notify CALICO or its local representative, giving full details of the difficulty, and including the model number and serial number. On receipt of this information, service data or shipping instructions will be furnished. If shipment is indicated, forward the instrument, freight prepaid, to the factory or to the authorized repair station indicated in the instructions. If requested, an estimate of the charges will be made before the work begins, provided the instrument is not covered by the warranty.

DAMAGE IN TRANSIT

The instrument should be tested as soon as it is received. If it fails to operate properly, or is damaged in any way, a claim should be filed with the carrier. A full report of the damage should be obtained by the claim agent, and this report should be forwarded to us. CALICO will advise the disposition to be made of the equipment and arrange for repair or replacement. Please include model number and serial number when referring to the instrument.

SPARE PARTS ORDERING INFORMATION

In order to provide our customers with prompt service on component parts procurement for ělin equipment, please follow the instructions below.

When ordering component parts, DELETE THE LETTER PREFIX that may appear in the ělin part number, EXCEPT in the case of TRANSFORMER orders.

Ordering information must include the ělin part number and a description of the part.

Example: ělin part number 73721, potentiometer, 25 ohms, 2 watt.

If possible, include the manufacturer's name and part number as well as the model number and serial number of the instrument.

Example: ělin part number 73721, potentiometer, 25 ohms, 2 watt, Clarostat 43C2, for Model RK-102, serial number 0036.

TABLE OF CONTENTS

PAGE NO.

SPECIFICATION SHEET

1

GENERAL DESCRIPTION

SECTION 1

- 1.0 Introduction 2
- 1.1 Unpacking and Mechanical Inspection.. 2
- 1.2 Electrical Connections 2

SECTION 2

- 2.0 Controls 3
- 2.1 General Operating Information 3

THEORY OF OPERATION

SECTION 3

- 3.0 Wien Bridge Oscillator 4
- 3.1 Two-watt Amplifier 4
- 3.2 Power Supply 4

MAINTENANCE & TROUBLE SHOOTING NOTES

SECTION 4

- 4.0 General Information 5
- 4.1 Calibration 5

BLOCK DIAGRAM 4

TUBE & ADJUSTMENT LOCATION DRAWING 6

PARTS LIST 7,8

SCHEMATIC 9



Digitized by the Internet Archive
in 2025

https://archive.org/details/manualsplus_05545

SPECIFICATIONS

MODEL ADO-102

FREQUENCY RANGE:	10 CPS TO 100 KC IN FOUR DECADE RANGES
CALIBRATION ACCURACY:	$\pm 1\%$ @ 25°C WITH THE FINE FREQUENCY VERNIER CENTERED (CAN BE ADJUSTED TO 0% BY FINE FREQUENCY VERNIER)
FREQUENCY STABILITY:	$\pm 0.5\%$, 15 TO 45°C , ALL CONDITIONS OF LINE & LOAD*
FREQUENCY RESPONSE:	LESS THAN ± 0.25 DB OVER MOST OF THE RANGE, RISING TO ± 1 DB AT THE EXTREMES (REFERENCE - 1KC)
OUTPUT VOLTAGE:	0 - 50V RMS IN FOUR DECADE RANGES
OUTPUT POWER:	2VA @ 50V OUTPUT **
LOAD REGULATION:	LESS THAN 0.25% AT FULL OUTPUT VOLTAGE
TOTAL HARMONIC DISTORTION:	LESS THAN 0.1% AT FULL LOAD OVER MOST OF THE RANGE, RISING TO 0.1% AT 100 CPS
THD, NOISE AND JITTER:	LESS THAN - 66 DB OF FULL OUTPUT VOLTAGE

* LINE: 105 TO 125V

** UNIT IS STABLE WITH PURE RE-
ACTIVE LOAD, EITHER LEAD OR LAG.

1. INTRODUCTION

The new ADO-102 utilizes the latest engineering developments integrated with established techniques, to provide the ultimate in an audio signal generator.

This instrument combines simplicity of operation with a new and sophisticated approach to the generation of AC signals. The utilization of Elin's unique solid-state regulator in a time-honored Wien Bridge oscillator circuit provides an ultra stable, low distortion AC signal which in turn drives an amplifier capable of delivering more than 2VA output.

The amplifier adds little or no distortion to the extremely pure output of the oscillator.

The features, combined with a simplicity of operation and direct readout, lend themselves to an almost infinite number of applications throughout the electronic industry.

2. PACKING AND MECHANICAL INSPECTION

Inspect instrument for shipping damage as soon as it is unpacked. Visually inspect the instrument for broken knobs, connectors or any other signs of physical damage. Rotate controls and switches for smoothness of operation. Binding or jamming indicates defective mechanical operation. If a control is found that does not turn freely, do not force it for such action may cause serious damage. Upon satisfactory visual inspection, check the electrical performance of the instrument. If instrument is defective, see the warranty page 1.

(A) recommends that the instrument panel and its controls be grounded for safety of operation. All Elin instruments are equipped with a three-conductor power cord which when plugged into an appropriate receptacle will ground the instrument. The ground pin on the power cord three-prong connector is the offset round pin. When operating the instrument from a two-contact outlet, use a three-prong to two-prong adapter and connect the ground prong on the adapter to ground.

WIEN BRIDGE OSCILLATOR ELIN ASSY. 96026

The oscillator section of the ADC-102 is a capacitance-resistance tuned Wien Bridge Circuit. Precision metal film resistors and ultra-stable polystyrene capacitors are used in the tuning circuits to insure stable operation.


Referring to the block diagram, below, a "compactron" 6D10 and a 12B4 make up the tube complement of the oscillator. The "Solid State Regulator", Elin Part No. 96024, is used to keep the oscillator voltage constant at approximately thirty volts. This regulator serves the same function as a lamp without the inherent mechanical instability associated with lamp stabilization.

TWO-WATT AMPLIFIER ELIN ASSY. 96028

The amplifier section of the ADC-102 consists of a 12AU7 voltage amplifier, 12B4 phase splitter and a pair of 12B4's connected as a push-pull cathode follower. This configuration, in conjunction with a large amount of inverse voltage feedback, creates an amplifier capable of more than two-watts output with the addition of very little total harmonic distortion.

POWER SUPPLY

The power supply section of the ADC-102 consists of a full-wave voltage doubler AC supply and an electronic regulator. The electronic regulator is made up of a 7233 pass-tube and a zener diode referenced control unit, Elin Assy. 96027. Use of a regulated B+ voltage minimizes the effects of line variations on the instrument.



Maintenance on the AD-102 should be very limited due to conservative rating of components and use of the IFR dissipating tube shields; however, should failure occur, a systematic approach to the problem can be followed. The trouble shooting information presented in this section is for the use of personnel thoroughly used in trouble shooting procedures and the circuitry given in Section 1.

Fuse located on the front panel should be checked.

Alternating current supplied to the power transformer could be measured to insure that the input voltage is within the range of 115 to 125 VRT, 50 to 60 cps.

5A tubes should be checked by direct substitution.

Voltage measurements should be made to determine if all voltages are correct. The nominal voltages are marked on the schematic. All voltages should vary $\pm 2\%$ from the designated voltage. Measurements should be made with a vacuum tube voltmeter.


Standard signal tracing procedures can be used with this instrument. Use a scope with a high impedance probe to prevent signal loading.

Distortion may be measured with an instrument which directly indicates percentage of total harmonic distortion, such as a Hewlett-Packard Model 338.

TUNING

approximately one hour warm-up before checking frequency calibration. The fine frequency vernier should be checked since its range is $\pm 2\%$ of the set frequency. There are no adjustments since the component tolerances more than insure accurate calibration.

TUBE AND ADJUSTMENT LOCATION DRAWING



REAR VIEW WITH COVER REMOVED

IERC

INTERNATIONAL ELECTRONIC RESEARCH CORP
135 W. MARSHALL BLVD. BURBANK, CALIFORNIA

STATUS

PROP REL
APP
STK REL
COMPL

APP

ITEM	REFERENCE DES	QTY	ELN PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL
1		Ref	A86172	Spec Sheet	A86172	Elin 12897				
2		1	D11132	Panel, Front	D11132	Elin 12897				
3		1	D25014	Chassis	D25014	Elin 12897				
4		2	C67082	Plate, Chassis, Side	C67082	Elin 12897				
5		1	D67086	Plate, Switch Mtg.	D67086	Elin 12897				
6		1	B67085	Plate, Chassis, Rear	B67085	Elin 12897				
7		2	B34027	Cover, Top & Bottom	B34027	Elin 12897				
8		5	A42005	Fastener, Hub	A42005	Elin 12897				
9		3	B37004	Dial (0-10)	B37004	Elin 12897				
10		1	B37005	Dial (0-00)	B37005	Elin 12897				
11		1	B37006	Dial (50-Off)	B37006	Elin 12897				
12		1	B16051	Bracket, Connector Mtg.	B16051	Elin 12897				

[illegible]

ITEM	QUANTITY	ALN PART NO	DESCRIPTION	MFG. PART NO	MFG OR CODE NO.	STK	P O NO	UNIT PRICE	TOTAL
34	R1, R2	7302 473-5	Resistor, Composition 47K, 2W, 5%	IB-4735	Allen Bradley 01121				
35	R3	73410- 352	Resistor, Wire Wound 3.5K, 10W, ±10%	4836A	Ohmite 44655				
36									
37									
38	C1, C3, C4	21041	Capacitor, Electro- lytic 260uf @ 300V	SP020-7666B	Mallory 37942				
39	C2A, C2B	21046	Capacitor, Elect. 50V Dual, 35mf @ 400V & 100mf	FP 229	Mallory 37942				
40									
41									
42	F1	45001	Fuse, Slo-Blo 1 amp	313001	Little Fuse 75915				
43	XF1	45500	Fuse Holder	342004	Little Fuse 75915				
44	J1	29021-1	Connector	UG 657/U	Cannon 71468				
45	P1	29521	Connector	UG 88/U	Cannon 71468				
46	IS1, 2, 3	54008	Assy, Pilot Lamp 12 V White	18P3-6397	Edgema 03707				
47	W1	32003	Cord, Line	183SJT	Electro Cord				
48	J2	90000	Binding Post, Red	DF31RC	Superior Elect 58474				
49	J3	90001	Binding Post, Black	DF31BC	Superior Elect. 58474				
50		91020	Terminal Lug	RB14-10	Thomas & Betts 59730				
51		50004	Wafer, Cap. Mtg.	BP6	Mallory 37942				
52		27001	Bushing, Strain Relief SR-6P-1		Keyman 28520				
53		91021	Terminal Strip 3 Lug + Grd.	4-1118	Alcon				
54		91022	Terminal Strip 2 Lug + Grd.	4-1059	Alcon				

ITEM	REFERENCE DES	QTY	P/N PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO.	STK	P O NO	UNIT PRICE	TOTAL
55	TB 4	1	91023	Terminal Strip 1 Lug	4-1007	Alcon				
56		2	27048	Clamp Cable 3/16 dia.	832	H.H. Smith 83330				
57		1	81014	Socket, 9 pin min.	952LL-7	Alcon				
58		1	80044	Shield Base	950	Alcon				
59		1	80042	Dissipator, Tube	TRT6-6025	I.E.R.C. 98978				
60		2	49033	Handles	FCA-8	Vemaline				
61		3	52002	Knob	RB900	Rogan 86797				
62		2	52003	Knob, Dual, Small Knob, Red w/White Line Large Knob, Black 1/4", 1/8" shaft	RB999-700	Rogan 86797				
63		3	87003	Spring, Pilot Light	111	Western Spring				
64	A/R	20004		Cable, Coax.	RG-59/u	F. T. & R.				
65		4	61028	Tinnerman Nut	C8032-832	Tinnerman Prod.				

PRODUCTION RELEASE			BILL OF MATERIALS				PAGE 1 OF 3			
APPROVED BY _____			INTERNATIONAL ELECTRONIC RESEARCH CORP.				PROJECT/JOB NO.			
STOCK RELEASE DATE _____			135 W. MAGNOLIA BLVD., BURBANK, CALIFORNIA				1.0.P. 11-27-4			
COMPLETION DATE _____			OSCILLATOR WIEN BRIDGE				DESIGNANT ENGINEER			
							SCHEMATIC			
							C96026 G			
SYM.	DESCRIPTION	COMMENTS	APPROVED MFR. & MFR. DESIGNATION	QTY.	PART NO.	INSP. CODE	STK.	P.O. NO.	UNIT PRICE	TOTAL
V-1	TUBES ELECTRON		GE	1	6D10					
V-2	"		"	1	1284A					
R-12	RESISTORS 1.5 K 1/2W 10%	CARBON COMP.	ALLEN-BRADLEY	1	7300.5-152-10					
R-11	4.7 K "	"	"	1	7300.5-472-10					
R-8	82 K "	"	"	1	7300.5-823-10					
R-1,15	270 K "	"	"	2	7300.5-274-10					
R-9	1.5 M "	"	"	1	7300.5-155-10					
R-10	2.2 M "	"	"	1	7300.5-225-10					
R-14	3.3 M "	"	"	1	7300.5-335-10					
R-7	27 K 1W "	"	"	1	7301-273-10					
R-13	24 K 2W "	"	"	1	7302-243-10					
R-5	2.37 K 1/2W 1%	DEP. CARBON	1.1. TYPE CD 1/2MR	1	7310.5-2371-1					
R-6	3.48 K "	"	"	1	7310.5-3481-1					
R-2	6.19 K "	"	"	1	7310.5-6191-1					

elin INSTRUMENTS

INTERNATIONAL ELECTRONIC RESEARCH CORP
135 W MAGNOLIA BLVD., BURBANK, CALIFORNIA

IERC

STATUS

PROD REL
APP

STK REL
COMPL

ITEM	REFERENCE DES	QTY	ELIN PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL
22		3	78057	Screw Binder H1D 3-48 x 3/16 lg. Nic.Pl. lockwasher, Int.Tooth						
23		3	94005	#2 CAD.Pl.						
24		2	61025	Hex. Nut, Radio #1-48 Nic.Pl.						
26				Wire #22 AWG. Red 1050C						
27				Bunch Tinned 2" lg. Strip 1/4" each end.						
28										
29				Wire #22 AWG, solid tinned 1 1/2"						

APPROVED BY:	INTERNATIONAL ELECTRONIC RESEARCH CORP	PROJECT: JOB NO
STOCK RELEASE DATE:	135 W. MAGNOLIA BLVD., BURBANK, CALIFORNIA	2M AMPLIFIER
COMPLETION DATE:	COMPL BY: DATE	SCHEMATIC
	N. PAIK 4-23-62	C96028 E

SYM.	DESCRIPTION	COMMENTS	APPROVED MFR. & MFR DESIGNATION	QTY	PART NO	STOCK	P.O. NO.	UNIT PRICE	TOTAL
V-2,3,4	TUBES 12B1A		GE	3	12B1A				
V-1	12AU7A		"	1	12AU7A				
F-9-10	RESISTORS 1.5K 1/2W 5%	CARB. COMP.	ALLEN-BRADLEY	2	7300.5-152-5				
R-13	4.7K " "	"	"	1	7300.5-472-5				
R-7,11	1M " 10%	"	"	2	7300.5-103-10				
R-3,4	33K 1W "	"	"	2	7301-333-10				
R-14	1K 2W 5%	"	"	1	7302-102-5				
R-5	24K " 10%	"	"	1	7302-243-10				
R-1	56.2K 1/2W 1%	DEP. CARB.	T.I. TYPE CC1/2MR	1	7310.5-5622-1				
R-2	100K " "	"	"	1	7310.5-104-1				
C-4	CAPACITORS 2200 PF ± 10% @ 400V	MYLAR	AJAX TYPE PPW	1	2224-222-10A				
C-6	.01 UF " "	"	"	1	2224-103-10A				
C-5	.47 UF ± 20% "	"	ELPAC 2D-4A474	1	2224-474-20A				
C-3	2 UF " "	"	ELECTRON D4-205	1	2224-205-20A				

APPROVED BY

STOCK RELEASE DATE

COMPLETION DATE

elin division

COMPILED BY: N. PAIK

DATE: 4-23-63

INTERNATIONAL ELECTRONIC RESEARCH CORP
135 W. MAGNOLIA BLVD., BURBANK, CALIFORNIA

DESIGNING ENGINEER

N. PAIK

CUSTOMER

TIME
2W

SPECS

2W AMPLIFIER

SCHEMATIC

C96018 E

SYM.	DESCRIPTION	COMMENTS	APPROVED MFR. & MFR DESIGNATION	QTY	PART NO	STOCK	P.O. NO.	UNIT PRICE	TOTAL
C-7,8	CAPACITORS CONTINUED 220 PF 5% 500V	EURA MICA	ELMENDO DN-15-221J	2	2235-221-5				
C-1,2	2 PF 20%	"	" CM-15-020K	2	2235-020-20				
	TUBE COMPONENTS								
	FIELD		194C TRT6-0025B	3	80042				
	SHIELD		" TRT6-5020B	1	80043				
	SOCKET, 9-PIN	MICA FILLED W/ GND LUGS - CENT. SADDLE	ALCON 925LL-7	4	81014				
	CASE, SHIELD		ALCON 95C	4	80047				
	MISCELLANEOUS PLATE, CHAUSIS		APC	1	B670903				
	TERMINAL STRIP	3-LUG MIN.	ALCON 4-01772	1	91017				
	TERMINAL STRIP	1-LUG MIN.	" 4-01772	1	91018				

IERC

elin

INTERNATIONAL ELECTRONIC RESEARCH CORP
135 W. MAGNOLIA BLVD., BURBANK, CALIFORNIA

INSTRUMENTS

APP

PROD REL

STATUS

STA REL

COMPL

APP

PROD REL

STATUS

ITEM	REFERENCE DES	QTY	FLIN PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL
------	---------------	-----	--------------	-------------	-------------	----------------	-----	--------	------------	-------

1	S5	1	89518B	Switch, Rotary	218720 J2C	Oak 76854				
2										
3										
4	R8	1	7310-5	Resistor, Dep. Carbon 2490hm 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
5	R6	1	7310-5	Resistor, Dep. Carbon 24.9ohm 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
6	R7	1	24.90-1	Resistor, Wire Wound		IRC				
7	R5	1	73690	Resistor, 2W, ±1% Carbon	AS2	75042				
8	R4	1	7312-	Resistor, 2W, ±1% Carbon	Type CR 2R	Texas Inst. 01295				
9	R10, 11	2	2491-1	Resistor, Composition	EB 2231	Allen Bradley				
10			7300-5	22K, 1/2W, ±10%		01121				
11			223-10	Resistor, Composition	HB-2435	Allen Bradley				
12	C1	1	7302-243-5	Capacitor, Electro-lytic 40uf @ 250V	TC 58	Mallory 76149				

ITEM	REFERENCE DES	QTY	FLY PART NO	DESCRIPTION	MFG. PART NO.	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL
1	S4	1	89517B	Switch, Rotary		Oak 76854				
2										
3										
4	C1A, C2A	2	2252-5283-0.5A	Cap. Polystyrene .528ufd $\pm 1/2\%$ 200V	PW5283F2AT	Southern Electric				
5	C1B, C2B	2	2252-533-0.5A	Cap. Polystyrene .053ufd $\pm 1/2\%$ 200V	2PJ533D	Arco 84171				
6	C1C, C2C	2	2252-532-0.5B	Cap. Polystyrene .0053ufd $\pm 1/2\%$ 200V	2PJ532D	Arco 84171				
7	C1D, C2D	2	2252-501-1A	Cap. Polystyrene .0005ufd $\pm 1/2\%$ 200V	2PJ501D	Arco 84171				
8	C1E	1	2235-330-5	Cap. Sil. Mica 33pf $\pm 5\%$ 500V	DM10-330J	Elmenco 02799				
9										
10										
11	R3	1	7320.5-29261-0.5	Resistor, Metal Film 29.26K $\pm 1/2\%$, 1/2W	WL70 T3A	Ward Leonard 63473				

IERC				elin				INSTRUMENTS				INTERNATIONAL ELECTRONIC RESEARCH CORP				135 W MAGNOLIA BLVD., BURBANK, CALIFORNIA				STATUS			
APP				PROP REL				STK REL				COMPL											
APP				PROP REL				STK REL				COMPL											
ITEM	REFERENCE DES	QTY	ELIN PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL													
1	S1	1	89519B	Switch, Rotary		Oak 22838-J3C 76854																	
2																							
3																							
4	R6A-1, R2A-1	2	7320-5	Resistor, Metal Film		Ward Leonard 63743																	
5	R6A-2, R2A-2	2	1482-0.5	14.8K 1/2W, 1/2%	Type WL70T3A	Ward Leonard 63743																	
6	R6A-3, R2A-3	2	7320-5	Resistor, Metal Film		Ward Leonard 63743																	
7	R6A-4, -5	3	9751-0.5	9.75K 1/2W, 1/2%	Type WL70T3A	Ward Leonard 63743																	
8	R6A-6	1	7320-5	Resistor, Metal Film		Ward Leonard 63743																	
9	R6A-7	1	7300-5	7.38K 1/2W, 1/2%	Type WL70T3A	Ward Leonard 63743																	
10	R6A-8	1	824-10	Resistor, Carbon		Allen Bradley 01121																	
11	R6A-9	1	7300-5	Comp. 820K, 1/2W, ±10%	Type WL70T3A	Allen Bradley 01121																	
12			7300-5	Resistor, Carbon		Allen Bradley 01121																	
13	C-R2A-3	1	105-10	Resistor, Carbon		Allen Bradley 01121																	
14	C-R2A-2	1	7300-5	2.7M 1/2W, ±10%	EB-275-10	Allen Bradley 01121																	
15	C-R2A-4	1	7300-5	1.5M 1/2W, ±10%	EB-155-10	Allen Bradley 01121																	
				Capacitor, Sil. Mica		Elmenco 02799																	
				15pf ±5%, 50 V	DM10-150J	Elmenco 02799																	
				Capacitor, Sil. Mica		Elmenco 02799																	
				20pf ±5%, 500V	DM10-200J	Elmenco 02799																	
				Capacitor, Sil Mica		Elmenco 02799																	
				10pf ±5%, 500V	DM10-100J	Elmenco 02799																	

INTERMEDIATE SALES & ENGINEERING RESEARCH CORP.
135 W. MAGNOLIA BLVD., BURBANK, CALIFORNIAPROJ. NO. STA. REC.
APP. COMPL.

ITEM	REFERENCE	QTY	PART NO.	DESCRIPTION	MFG. PART NO.	MFG. OR CODE NO.	STR.	P.O. NO.	UNIT PRICE	TOTAL
1	S2	1	89520A	Switch, Rotary	218721 J2C	Oak 76854				
2										
3										
4	R6B-1 R2B-1	2	7310.5-3013-1	Resistor, Carbon Dep. 301K, 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
5	R6B-2 R2B-2	2	7310.5-1473-1	Resistor, Carbon Dep. 147K 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
6	R6B-3 R2B-3	2	7310.5-9762-1	Resistor, Carbon Dep. 97.6K, 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
7	R6B-4 R2B-4	2	7310.5-7322-1	Resistor, Carbon Dep. 73.2K, 1/2W, ±1%	Type CD1/2MR	Texas Inst. 01295				
8										
9										
10	C R2B-4 C R2B-3	2	2235-20-20	Capacitor, Sil. Nica 2pf ±20%	DM10-020	Elmenco 02799				

IERC

elin

INSTRUMENTS
INTERNATIONAL ELECTRONIC RESEARCH CORP
135 W MAGNOLIA BLVD., BURBANK, CALIFORNIAPROD. REL
APP

STATUS

STK. REL

COMPL.

APP

ITEM	REFERENCE DES	QTY	ELIN PART NO	DESCRIPTION	MFG PART NO	MFG OR CODE NO	STK	P O NO	UNIT PRICE	TOTAL
1	S3	1	89520A	Switch, Rotary		218721 J2C				
2										
3										
4	R6C-4, R2C-4	2	7310.5 754-1	Resistor, Carbon Dep. 750K, 1/2W, $\pm 1\%$	Type CD1/2MR	Texas Inst. 01295				
5	R6C-3, R2C-3	2	7310.5- 105-1	Resistor, Carbon Dep. 1M, 1/2W, $\pm 1\%$	Type CD1/2MR	Texas Inst. 01295				
6	R6C-2, R2C-2	2	7310.5- 155-1	Resistor, Carbon Dep. 1.5M, 1/2W, $\pm 1\%$	Type CD1/2MR	Texas Inst. 01295				
7	R6C-1, R2C-1	2	7310.5- 305-1	Resistor, Carbon Dep. 3M, 1/2W, $\pm 1\%$	Type CD1/2MR	Texas Inst. 01295				
8										
9										
10	C3	1	2235-50-10	Capacitor, Sil. Mica 5pf $\pm 10\%$	DM10-050K	Elmenco 02799				
11	C R2C-3 C-R2C-4	2	2235-20-20	Capacitor, Sil. Mica 2pf, $\pm 20\%$	DM10-020	Elmenco 02799				

BILL OF MATERIALS

ON ROOM

1

1000

elin division

2
3
4
5
6
7
8
9
10
11
12
13
14
15
16
17
18
19
20
21
22
23
24
25
26
27
28
29
30
31
32
33
34
35
36
37
38
39
40
41
42
43
44
45
46
47
48
49
50
51
52
53
54
55
56
57
58
59
60
61
62
63
64
65
66
67
68
69
70
71
72
73
74
75
76
77
78
79
80
81
82
83
84
85
86
87
88
89
90
91
92
93
94
95
96
97
98
99
100
101
102
103
104
105
106
107
108
109
110
111
112
113
114
115
116
117
118
119
120
121
122
123
124
125
126
127
128
129
130
131
132
133
134
135
136
137
138
139
140
141
142
143
144
145
146
147
148
149
150
151
152
153
154
155
156
157
158
159
160
161
162
163
164
165
166
167
168
169
170
171
172
173
174
175
176
177
178
179
180
181
182
183
184
185
186
187
188
189
190
191
192
193
194
195
196
197
198
199
200
201
202
203
204
205
206
207
208
209
210
211
212
213
214
215
216
217
218
219
220
221
222
223
224
225
226
227
228
229
230
231
232
233
234
235
236
237
238
239
240
241
242
243
244
245
246
247
248
249
250
251
252
253
254
255
256
257
258
259
260
261
262
263
264
265
266
267
268
269
270
271
272
273
274
275
276
277
278
279
280
281
282
283
284
285
286
287
288
289
290
291
292
293
294
295
296
297
298
299
300
301
302
303
304
305
306
307
308
309
310
311
312
313
314
315
316
317
318
319
320
321
322
323
324
325
326
327
328
329
330
331
332
333
334
335
336
337
338
339
340
341
342
343
344
345
346
347
348
349
350
351
352
353
354
355
356
357
358
359
360
361
362
363
364
365
366
367
368
369
370
371
372
373
374
375
376
377
378
379
380
381
382
383
384
385
386
387
388
389
390
391
392
393
394
395
396
397
398
399
400
401
402
403
404
405
406
407
408
409
410
411
412
413
414
415
416
417
418
419
420
421
422
423
424
425
426
427
428
429
430
431
432
433
434
435
436
437
438
439
440
441
442
443
444
445
446
447
448
449
450
451
452
453
454
455
456
457
458
459
460
461
462
463
464
465
466
467
468
469
470
471
472
473
474
475
476
477
478
479
480
481
482
483
484
485
486
487
488
489
490
491
492
493
494
495
496
497
498
499
500
501
502
503
504
505
506
507
508
509
510
511
512
513
514
515
516
517
518
519
520
521
522
523
524
525
526
527
528
529
530
531
532
533
534
535
536
537
538
539
540
541
542
543
544
545
546
547
548
549
550
551
552
553
554
555
556
557
558
559
560
561
562
563
564
565
566
567
568
569
570
571
572
573
574
575
576
577
578
579
580
581
582
583
584
585
586
587
588
589
590
591
592
593
594
595
596
597
598
599
600
601
602
603
604
605
606
607
608
609
610
611
612
613
614
615
616
617
618
619
620
621
622
623
624
625
626
627
628
629
630
631
632
633
634
635
636
637
638
639
640
641
642
643
644
645
646
647
648
649
650
651
652
653
654
655
656
657
658
659
660
661
662
663
664
665
666
667
668
669
670
671
672
673
674
675
676
677
678
679
680
681
682
683
684
685
686
687
688
689
690
691
692
693
694
695
696
697
698
699
700
701
702
703
704
705
706
707
708
709
710
711
712
713
714
715
716
717
718
719
720
721
722
723
724
725
726
727
728
729
730
731
732
733
734
735
736
737
738
739
740
741
742
743
744
745
746
747
748
749
750
751
752
753
754
755
756
757
758
759
760
761
762
763
764
765
766
767
768
769
770
771
772
773
774
775
776
777
778
779
780
781
782
783
784
785
786
787
788
789
790
791
792
793
794
795
796
797
798
799
800
801
802
803
804
805
806
807
808
809
810
811
812
813
814
815
816
817
818
819
820
821
822
823
824
825
826
827
828
829
830
831
832
833
834
835
836
837
838
839
840
841

COMPILED BY: DATE
NEW YORK 4-23-62

REGULATOR SOLID STATE ASSEMBLY

COUNIZANT ENGINEER


SCHEMATIC

CON: 4B


[illegible]

514 division of INTERNATIONAL ELECTRONIC RESEARCH CORP. claims proprietary and/or patent right in the material disclosed herein. This drawing is issued in confidence for engineering information only and may not be reproduced or used to manufacture anything shown hereon without direct written permission from 514 division of INTERNATIONAL ELECTRONIC RESEARCH CORP. to the user.

REVISION		DATE	APPROVED
E	REDRAWN, CIRCUIT UNCHANGED	7/19/65	7/23/65
F	ADDED VALUES TO R1A & R1B	2-22-71	97



C96026



MP MASTER



MA28054